

10ft ISO UNIVERSAL FULL FRAME OFFSHORE TANK (DNV-Approved)



Key Information

CAPACITY	:	2000 US Gallons, - 2% + 2% (7580 litres nominal)
TARE WEIGHT	:	2400kg nominal.
MAX GROSS	:	13,000kg
PRESSURE	:	4.0 bar (working); 6.0 bar (test).
DESIGN TEMP.	:	-20 to 65°C.
TYPE APPROVALS	:	T11 UN Portable tank (incl. IMDG and ADR), TIR, CSC, EN 12079, DNV 2.7-1.
SHELL MATERIALS	:	316/316L Stainless steel (1.4401/1.4404).
FRAME	:	ISO 668 ID - 10' Long x 8' Wide x 8' high Empty-lift fork pockets, 4 off lifting lugs, galvanised steel or aluminium walkway and ladder to rear.
SLINGS	:	Wire rope sling set to DNV 2.7-1 & EN 12079
TANK FITTINGS	:	Safety relief valve, airline, 500mm dia. manway, 3" Bottom outlet. Optional: airline operational from ground level, Level gauge
INSULATION & CLADDING	:	Available as option if required.
PAINT SYSTEM	:	All mild steel parts shotblasted to SA 2 ½". One coat Hempel 1536 zinc rich epoxy primer 30 MDFT. One coat Hempthane 5521 to 80 MDFT.