

*4000 litre VERTICALLY MOUNTED OFFSHORE
TANK (DNV-Approved)*



Key Information

CAPACITY	:	4000 litres, - 2% + 2% (1050 USG nominal)
TARE WEIGHT	:	1950kg nominal.
MAX GROSS	:	8,000kg
PRESSURE	:	2.67 bar (working); 4.0 bar (test).
DESIGN TEMP.	:	-20 to 65°C.
TYPE APPROVALS	:	T7 UN Portable tank (incl. IMDG and ADR), TIR, CSC, EN 12079, DNV 2.7-1.
SHELL MATERIALS	:	316/316L Stainless steel (1.4401/1.4404).
FRAME	:	1995mm long x 1995mm wide x 2571mm high Empty-lift fork pockets, 4 off lifting lugs, galvanised steel walkway and ladder to rear.
SLINGS	:	Wire rope sling set to DNV 2.7-1 & EN 12079
TANK FITTINGS	:	Safety relief valve, airline, 460mm dia. manway, 2" Bottom outlet. Optional: airline operational from ground level, Level gauge
PAINT SYSTEM	:	All mild steel parts shotblasted to SA 2 ½". One coat Hempel 1536 zinc rich epoxy primer 30 MDFT. One coat Hempathane 5521 to 80 MDFT.